

<pre> HttpResponse.BodyHandler (interface) apply(..) HttpResponse.BodyHandlers fromSubscriber(Flow.Sub) fromSubscriber(Flow.Sub, Function) fromLineSubscriber(Flow.Sub, ..) fromLineSubscriber(Flow.Sub, Function) ofByteArray() ofByteArrayConsumer(..) ofFile(Path) ofFile(Path, OpenOptions...) ofFileDownload(Path) ofInputStream() ofLines() ofString() ofString(Charset) buffering(..) discarding(..) replacing(..) </pre>	<pre> HttpResponse.BodySubscriber (interface) getBody() HttpResponse.BodySubscribers fromSubscriber(Flow.Sub) fromSubscriber(Flow.Sub, Function) fromLineSubscriber(Flow.Sub, ..) fromLineSubscriber(Flow.Sub, Function) ofByteArray() ofByteArrayConsumer(..) ofFile(Path) ofFile(Path, OpenOptions...) ofInputStream() ofLines(Charset) ofString(Charset) buffering(..) discarding(..) mapping(..) replacing(..) </pre>	<pre> HttpRequest.BodyPublisher (interface) contentLength() HttpRequest.BodyPublishers fromPublisher(Flow.Pub) fromPublisher(Flow.Pub, Function) ofByteArray(ba) ofByteArray(ba, off, len) ofByteArrays(Iterable(ba)) ofFile(..) ofInputStream(..) ofString(String) ofString(String, Charset) noBody() </pre>
<p>fromXxx: Adapters from standard Subscriber, e.g. takes a Flow.Subscriber returns a BodySubscriber.</p> <p>ofXxx: Factories that create a new pre-defined Body[Handler Subscriber], that perform useful common tasks, like handling the response body as a String, or streaming it to a File.</p> <p>green: Combinators (takes a BodySubscriber returns a BodySubscriber) and other useful operations.</p> <p>There are subtle difference between the BH and BS similarly named methods, e.g. BH.ofString determines the Charset to use based on the value of the Content-Type header received.</p>		<p>fromXxx: Adapters from Flow.Publisher.</p> <p>ofXxx: Factories that create a new pre-defined BodyPublishers, that perform useful common tasks.</p> <p>green: Special publisher that publishes nothing, used in HEAD request, etc.</p>